



ES2A THRU ES2K

VOLTAGE RANGE 50 to 800 Volts
CURRENT 2.0 Ampere



Features

- Glass passivated chip
- Plastic package has underwrites laboratory flammability Classification 94V-0
- For surface mounted applications
- Low profile package
- Built-in strain relief, ideal for automated placement
- Glass Passivated chip junction
- High temperature soldering:250°C/10 second at terminals



DO-214AC (SMA)

Mechanical Data

- Case: JEDED DO-214AC molded plastic over glass passivated chip
- Terminals: Solder plated, Solderable per MIL-STD-750, method 2026
- Polarity: Color band denotes cathode end
- Weight: 0.0024ounce, 0.068 gram

Maximum Ratings and Electrical Characteristics

- Ratings at 25°C ambient temperature unless otherwise specified.
- Single phase, half wave, 60Hz, resistive or inductive load.
- For capacitive load derate current by 20%.

TYPE NUMBER		SYMBOLS	ES2A	ES2B	ES2C	ES2D	ES2E	ES2G	ES2J	ES2K	UNIT
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	50	100	150	200	300	400	600	800	Volts
Maximum RMS Voltage		V _{RMS}	35	70	105	140	210	280	420	560	Volts
Maximum DC Blocking Voltage		V _{DC}	50	100	150	200	300	400	600	800	Volts
Maximum Average Forward Rectified Current At T _A =100°C ^(NOTE 1)		I _(AV)	2.0								Amps
Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC Method)		I _{FSM}	50								Amps
Maximum Instantaneous Forward Voltage at 2.0A		V _F	0.95				1.25		1.70	1.95	Volts
Maximum DC Reverse Current at rated DC blocking voltage at	T _A = 25°C	I _R	5.0								μA
	T _A = 125°C		100								
Maximum Reverse Recovery Time ^(NOTE 3)		T _{RR}	35							50	nS
Typical Junction Capacitance ^(NOTE 2)		C _J	60				50				pF
Typical Thermal Resistance ^(NOTE 1)		R _{θJA}	70								°C/W
		R _{θJL}	28								
Operating Junction Temperature		T _J	-55 to +150								°C
Storage Temperature Range		T _{STG}	-55 to +150								°C

Notes:

1. Thermal resistance from Junction to ambient and from junction to lead mounted on P.C.B.with0.3×0.3"(8.0 × 8.0mm) copper pad areas.
2. Measured at 1.0MHz and applied reverse voltage of 4.0V
3. Test conditions $I_F = 0.5\text{A}$, $I_R = 1.0\text{A}$, $I_{RR} = 0.25\text{A}$



ES2A THRU ES2K

VOLTAGE RANGE 50 to 800 Volts
CURRENT 2.0 Ampere







Ratings and Characteristic Curves ($T_A=25^\circ\text{C}$ unless otherwise noted)FIG.1-TYPICAL FORWARD CURRENT
DERATING CURVEFIG.2-MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENTFIG.3-TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICSFIG.4-TYPICAL REVERSE
CHARACTERISTICS

FIG.5-TYPICAL JUNCTION CAPACITANCE

FIG.6-TEST CIRCUIT DIAGRAM AND
REVERSE RECOVERY TIME CHARACTERISTIC

NOTES : 1. Rise Time=7ns max. Input Impedance=1 magohm. 22pF
2. Rise time=10ns max. Source Impedance=50 ohms

SET TIME BASE FOR
50/100ns/cm




SURFACE MOUNT SUPER FAST RECTIFIER

ES2A THRU ES2K

VOLTAGE RANGE 50 to 800 Volts
CURRENT 2.0 Ampere

Package Outline Dimensions in inches (millimeters)






SURFACE MOUNT SUPER FAST RECTIFIER


ES2A THRU ES2K

VOLTAGE RANGE 50 to 800 Volts
CURRENT 2.0 Ampere

Package Reel Information




Specifications	Ao	Bo	Ko	Po	W	t1
SMA	2.55±0.10	5.10±0.10	2.36±0.10	4.00±0.1	12.0±0.05	0.23±0.02



DEVICE TYPE	Tape Width	13"Reel			07"Reel			
		Q'TY/REEL(pcs)	BOX/CARTOON	Q'TY/CARTON (pcs)	Q'TY/REEL(pcs)	REEL/BOX	BOX/CARTOON	Q'TY/CARTON (pcs)
SMA	12mm	5000	8	80000	1500	2	16	48000



Reflow Profile



Reflow Condition		Pb-Free Assembly
Pre Heat	Temperature Min.	+150°C
	Temperature Max.	+200°C
	Time(Min to Max)	60-180 secs.
Average ramp up rate(Liquidus Temp(T_L) to peak)		3°C/sec. Max.
$T_{S(max)}$ to T_L - Ramp-up Rate		3°C/sec. Max.
Reflow	Temperature (T_L)(Liquidus)	+217°C
	Temperature (T_L)	60-150 secs.
Peak Temp (T_P)		+(260+0/-5)°C
Time within 5°C of actual Peak Temp (T_P)		25 secs.
Ramp-down Rate		6°C/sec. Max.
Time 25°C to peak Temp (T_P)		8 min. Max.
Do not exceed		+260°C



ES2A THRU ES2K

VOLTAGE RANGE	50 to 800 Volts
CURRENT	2.0 Ampere

Disclaimer

The information presented in this document is for reference only. Chongqing changjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Changjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.czlangjie.com](http://www.czlangjie.com) , or consult your nearest Langjie's sales office for further assistance.