




A4						COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3								DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91938P124RS
A2						X.XX	± 0.10	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1						X.X	± 0.15	ROC CPU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION	ISSUE		X	± 0.25					
						ANGULAR	—	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basis of manufacture or sale of apparatus without permission				

A		B		C		D		E		F		G		
1	性能参数													
	1. Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A						13. mechanical: 500000cycles 机械寿命: 500000cycles							
	2. Rated current:3A/DC36V 额定电流:3A/DC36V						14. Operation method:Self-locking 操作方式: 自锁式							
	3. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ						15. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N							
	4. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ						16. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下							
	5. Pressing stroke:3.00mm ± 0.10 按压行程:3.00mm ± 0.10						17. LED lamp lifespan: 40000h LED寿命: 40000h							
	6. Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10						18. LED color: Red LED颜色: 红色							
	7. Nut assembly torque:5-14N 螺帽装配力矩:5-14N													
	8. Protection level:IP67 防护等级:IP67													
	9. Explosion prevention level: IK10 防暴等级: IK10													
2														
3	Working environment temperature: -20 ℃~+55 ℃ 工作环境温度: -20 ℃~+55 ℃													
	Compression torque: ≤ 4N 按压扭力: ≤4N													
	Electrical life: 50000 cycles 电气寿命: 50000 cycles													
	连接形式													
	1. Welding temperature of wire: 320 ± 20 ℃ 线材焊接温度: 320±20℃ Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下													
4														
5	A4				 台普 ROC PU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:		
	A3							DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91938P124RS		
	A2							DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw		
	A1							ROC PU TECHNOLOGY CO.,LTD						
	REV	DATE	REVISION	DESCRIPTION										ISSUE
	Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission													
	A		B		C		D		E		F		G	

A					B					C					D					E					F					G				
材质参数																																		
10					luminous zone 发光区					PC 塑料					1																			
9					LEDpin LED脚					Brass 黄铜					1					Silvering 镀银														
8					Base 底座					PA46					1																			
7					Pin 引脚					Brass 黄铜					1					gold-plating 镀金														
6					Contact material 接触材质					silver alloy 银合金					1																			
5					LED Base LED基座					PC 塑料					1																			
4					Arm nut 固定螺帽					Brass 黄铜					1					nickeling 镀镍														
3					Oring O型圈					Silica gel 硅胶					1																			
2					Housing 外壳					SUS 不锈钢					1																			
1					Key 按键					SUS 不锈钢					1																			
NO 序号					Part name 部件名					Material 材料					QTY 数量					Remark 备注														

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:	
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91938P124RS	
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw	
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD					
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR						
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission												