







A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:						
A3							DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91952P6BS						
A2						X.XX	± 0.10	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw					
A1						X.X	± 0.15	ROCPCU TECHNOLOGY CO.,LTD									
						X	± 0.25										
REV	DATE	REVISION	DESCRIPTION		ISSUE		ANGULAR	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basis of manufacture or sale of apparatus without permission									
				A		B		C		D		E		F		G	

A		B		C		D		E		F		G		
1	性能参数													
	1. Nut assembly torque:5-14N 螺帽装配力矩:5-14N													
	2. Protection level:IP67 防护等级:IP67													
	3. Explosion prevention level: IK10 防暴等级: IK10													
	4. Working environment temperature: -20 ℃~+55 ℃ 工作环境温度: -20 ℃~+55 ℃													
	5. LED voltage: 6V LED 电压: 6V													
	6. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下													
	7. LED lamp lifespan: 40000h LED寿命: 40000h													
2	8. LED color: Blue LED颜色: 蓝色													
3														
4	连接形式													
	1. Welding temperature of wire: 320 ± 20 ℃ 线材焊接温度: 320±20℃ Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下													
	2. Can be used with dedicated connectors: 可配专用接插件使用:													
	2.1 LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极													
5	A4				 台普 ROC PU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:		
	A3							DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO:TP91952P6BS		
	A2					X.XX	± 0.10	DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw		
	A1					X.X	± 0.15	ROC PU TECHNOLOGY CO.,LTD						
	REV	DATE	REVISION	DESCRIPTION		ISSUE	X							± 0.25
						ANGULAR	——	Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission						
	A		B		C		D		E		F		G	

		A	B	C	D	E	F	G
材质参数								
10								
9								
8								
7	luminous zone 发光区	PC 塑料	1					
6	LEDpin LED脚	Brass 黄铜	1		Silvering 镀银			
5	LED Base LED基座	PC 塑料	1					
4	Arm nut 固定螺帽	Brass 黄铜	1		nickeling 镀镍			
3	Oring O型圈	Silica gel 硅胶	1					
2	Housing 外壳	SUS 不锈钢	1					
1	Base 底座	PA46	1		Silvering 镀银			
NO 序号	Part name 部件名	Material 材料	QTY 数量		Remark 备注			

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:	
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91952P6BS	
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw	
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD					
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR						
Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission												