

| A |  | B |  | C    |             | D |         | E    |      |
|---|--|---|--|------|-------------|---|---------|------|------|
|   |  |   |  | REV. | DESCRIPTION |   | ECN NO. | NAME | DATE |
|   |  |   |  |      |             |   |         |      |      |

5

技术指标:

- |                                                                                       |  |                                               |               |               |                |  |                                                                                       |  |
|---------------------------------------------------------------------------------------|--|-----------------------------------------------|---------------|---------------|----------------|--|---------------------------------------------------------------------------------------|--|
| GENERAL TOLERANCE                                                                     |  | DONGGUAN BAOXUN PRECISION TECHNOLOGY CO., LTD |               |               |                |  |  |  |
| DIM. TOL.<br>X<br>X.X ±0.30<br>X.XX ±0.25<br>X.XXX ±0.15<br>GENERAL ANGLE: ±3°        |  | TITLE: 0.5 Pitch H2.0 Backflip R/A Type CONN  |               |               |                |  |  |  |
| DWG. NO.: FC-05BNP21H20                                                               |  |                                               |               |               | DRAWN: MAX     |  |                                                                                       |  |
| PART NO.: FC-05BNP21H20                                                               |  |                                               |               |               | CHECKED: ELLA  |  |                                                                                       |  |
| UNIT: mm                                                                              |  |                                               |               |               | APPROVED: WILL |  |                                                                                       |  |
|  |  | SCALE: none                                   | SHEET: 1 of 1 | DWG. SIZE: A4 | LAYER: bxconn  |  |                                                                                       |  |

Technical drawing of a reinforced concrete slab cross-section. The drawing shows a slab with a total width of 2.45 ± 0.05 m. The slab is supported by two columns, each with a width of 0.50 ± 0.05 m. The distance between the centerlines of the columns is 2.45 ± 0.05 m. The slab thickness is 0.178 m. The reinforcement consists of top bars (labeled 'CONN.') and bottom bars. The bottom bars are spaced at 0.35 ± 0.05 m. The top bars are spaced at 0.50 ± 0.05 m. The slab is shown with a cross-hatched pattern indicating the reinforcement. The drawing includes dimensions for the slab width, column width, and reinforcement spacing.

适用线路板(PCB LAYOUT)

