

OVD Series

Features

- 105°C, 15,000 hours assured
- Ultra low ESR, solid capacitors of SMD typp
- RoHS Compliant



Marking color: Blue

Specifications						Marking co	OI. DIUE			
Items	Performance									
Category Temperature Range	-55°C ~ +105°C									
Capacitance Tolerance		(at 120) Hz, 20°C)							
Leakage Current (at 20°C)*	Rated voltage applied, after 2 minutes at 20°C. See Standard Ratings									
Tanδ (at120 Hz, 20°C)	See Standard Ratings									
ESR (at 100k ~ 300k Hz, 20°C)	See Standard Ratings									
Endurance	Test Time 15,000 Hrs (6.3×4.4: 3,000 Hrs) Capacitance Change Within ± 20% of initial value Tanō Less than 150% of specified value ESR Less than 150% of specified value Leakage Current Within specified value * The above specifications shall be satisfied when the capacitors are restored to 20°C after the rated vo / 3,000 hours at 105°C.						or 15,000			
Moisture Resistance	Test Time 1,000 Hrs Capacitance Change Within ± 20% of initial value Tanō Less than 150% of specified value ESR Less than 150% of specified value Leakage Current Within specified value * The above specifications shall be satisfied when the capacitors are restored to 20°C after subjecting th					cting them at 60°C, 9	0 ~ 95%			
Resistance to Soldering Heat * (Please refer to page 15 for reflow soldering conditions)		Capao	Capacitance Change Within ± 10% of initial value Tanδ Within specified value ESR Within specified value Leakage Current Within specified value		0% of initial value pecified value pecified value pecified value					
Ripple Current and Frequency Multipliers	Frequency (H Multiplier		$\begin{array}{rl} 120 & \leq & f < 1k \\ & 0.05 \end{array}$	$\frac{1k}{0.3} \leq f < 10k$	$10k \le f < 100k$ 0.7	$100k \le f < 500k$ 1.0				

* For any doubt about measured values, measure the leakage current again after the following voltage treatment. Voltage treatment: DC rated voltage is applied to the capacitors for 2 hours at 105°C.

Diagram of Dimensions



Lead S	pacing and	Unit: mm					
φD	L A B C				W	Р	
5	5.8 ± 0.3	5.3	5.3	5.9	0.5 ~ 0.8	1.5	
6.3	4.4 ± 0.2	6.6	6.6	7.2	0.5 ~ 0.8	2.0	
6.3	5.8 ± 0.3	6.6	6.6	7.2	0.5 ~ 0.8	2.0	
The diagram is marking " () " for reference dimension.							

Marking





Standard Ratings

Dimension: $\phi D \times L(mm)$ Ripple Current: mA/rms at 100k Hz, 105°C

Rated Volt. (V)	Surge Voltage (V)	Capacitance (µF)	Size $\phi D \times L(mm)$	Tanδ (120 Hz, 20°C)	L C (μΑ)	E S R (mΩ/at 100k ~ 300k Hz, 20°C max.)	Rated R. C. (mA/rms at 100k Hz, 105°C)	
2.5V (0E) 2.9		220	6.3 × 4.4		300	19	2,780	
	2.0	220	5 × 5.8	0.12	412		3,500	
	2.9	330	6.3 × 4.4		700	16		
		560	6.3 × 5.8		700			
4V (0G) 4.6		180	6.3 × 4.4	0.12	360	19	2,780	
	4.6	220	5 × 5.8		440	17	3,390	
		390	6.3 × 5.8		780	17	3,390	
6.3V (0J) 7.2	150	6.3 × 4.4		472	19	2,780		
	7.0	180	5 × 5.8	0.12	567	17	3,390	
	1.2	220	6.3 × 4.4		4.4 700 18		18	3,200
		330	6.3 × 5.8		1,040	17	3,390	
16V(1C)	18.0	100	6.3 × 5.8	0.12	320	24	2,490	

Part Numbering System

OVD Series	100µF	± 20%	16V	Carrier Tape		$6.3 \phi \times 5.8 L$	General Purpose
OVD	<u>101</u>	M	<u>1C</u>	TR	-	<u>0606</u>	
Series Name	Capacitance	Capacitance Tolerance	Rated Voltage	Package Type	Terminal Type	Case Size	Application

Note: For more details, please refer to "Part Numbering System" on page 20.