

*MESSRS.*SPECIFICATION FOR APPROVAL
承 認 书

Product	DYNAMIC SPEAKER
Part No.	HDK-171208ZA-4C (RoHS)
Customer	
Customer Part No.	

Approved By	Checked By	Made By
王台平 MAY-20-2021	曹丽萍 MAY-20-2021	LILY MAY-20-2021

常州华龙电子有限公司

DRAGONSTATE ELECTRONIC CORPORATION

中国江苏省常州市新区电子园新四路 36 号

Tel: +86-519-85110078. 86-519-85106698, Fax: +86-519-85101081

EDITION:1. 1

1. Specification

HDK-171208ZA-4C (RoHS)

ITEM		SPECIFICATIONS
01	Type	Dynamic speaker
02	Dimension	External diameter 17×12 mm
03	Rated Input Power	0.7W
04	Max. Input Power	1.0W for 1 minute
05	Impedance	8 ohm $\pm$ 15% at 2500Hz 1.0V
06	Resonance Frequency (Fo)	800Hz $\pm$ 20% at Fo 1V
07	Sensitivity (S.P.L.)	94.5dB (0.7W / 0.1m) $\pm$ 3 dB at AVE 3KHz in a Baffle
08	Frequency Range	Fo - 20KHz
09	Dustproof and waterproof	IP67
10	Total Harmonics Distortion	Max 15 % at 1 KHz, 0.7W.
11	Voice Coil	Diameter 6.5 mm
12	Magnet	Rare earth permanent (Nd-Fe-B) magnet Φ 6.0 x 1.0 mm
13	Weight	1.5g $\pm$ 0.2g
14	Appearance	Should not exist any obstacle to be harmful to normal operation; damages, cracks, rusts and distortions, etc.
15	Operation Test	Must be normal at program source - 0.7W
16	Buzz, Rattle, etc.	Should not be audible at 2.36V sine Wave between Fo to 20KHz
17	Polarity	When positive voltage is applied to the terminal marked (+), diaphragm should move to the front.
18	Terminal Strength	Capable of withstand 1kg load for 30 seconds without resulting in any damage or rejection.
19	Temperature	Operating temperature: -30°C to +70°C Storage temperature: -40°C to +85°C

2-1. Test Condition

Standard

Temperature : 15 ~ 35℃

Relative humidity : 25% ~ 85%,

Atmospheric pressure : 860mbar to 1060mbar.

Basic

Temperature : 20±3℃

Relative humidity : 60% ~ 70%,

Atmospheric pressure : 860mbar to 1060mbar

2-2. Standard Test Fixture


1. Input Power : 0.7W (2.36V)

2. Zero Level : -dB

3. Mode : SPEAKER

4. potentiometer Range : 50dB

5. Sweep Time : 0.5sec



2-3. Frequency Response Curve






Table 1: Tolerance Limits Data for SPL


300	84	300	70
750	100	800	89
1200	101	1000	92
2000	99	1500	92
3300	97.5	3000	91.5
5000	100	4000	91.5
7000	101	7000	90






3. Dimension



4. Reliability Test

Items.		Specifications
01	High temp. Test	Keep 96 hours at $+85^{\circ}\text{C} \pm 3^{\circ}\text{C}$ and leave 3 hours in normal temperature and then check
02	Low temp. Test	Keep 96 hours at $-40^{\circ}\text{C} \pm 3^{\circ}\text{C}$ and leave 3 hours in normal temperature and then check
03	Humidity test	Keep 96 hours at $+40^{\circ}\text{C} \pm 3^{\circ}\text{C}$ relative humidity 95% and leave 3 hours in normal temperature and then checked.
04	Temp./Humidity cycle	The part shall be subjected 5 cycles. One cycle shall be 12 hours and consist of; 
05	Thermal cycle test.	Low temperature: $-40^{\circ}\text{C} \pm 3^{\circ}\text{C}$, temperature: $+85^{\circ}\text{C} \pm 3^{\circ}\text{C}$, cycle: 1 hour/cycle each, and then keep 5 cycles in a room.
06	Vibration	10~200~10Hz sin-wave sweep 15min. 5G(constant) X, Y, Z 3 direction. 2 hours each, total 6 hours.
07	Fix drop test	Fix on jig. Then drop from 152cm height to the concrete floor X, y, z 6 direction. 5 times each, total 30 times.
08	Free drop test	Free drop from 100cm height to the concrete floor X, y, z 6 direction. 1 times each, total 6 times.
09	Rated Power test	Rated Power Pink noise is applied for 100 hours
10	Max Power test	Max power 1 min on - 2 min off 10 cycles.
11	Terminal strength test	Capable of withstand 1kg load for 30 seconds without resulting in any damage or rejection.
12	Protection against liquids	Protected against 30 Minutes of immersion under 1M pressure Product without leakage
Criterion: After these test , the change of S.P.L shall be within ± 3 dB .		

5. Packing

REV NO.	REVISION NOTE	APPROVAL	DATE
 ↓  ↓  ↓  Cover(320*220*5mm) Material: Eps Box(320*220*13.5mm) 100pcs Material: Eps Middle(320*220*140mm) 1000pcs Material: Eps Outer Box(360*270*280mm) 4000pcs Material: Paper			
单位: mm			
TITLE: packing		DRAWN: Lily 2015/4/27	
PART NO.		SCALE: 2:1	
DWG NO.		SHEET: 1 of 1	
1		DESIGNED: R&D OF D.S.	
REV		CHECKED: Emily	
MATERIAL: ***		APPROVAL: Eric	
		UNITS: mm	
		TOLERANCE	
		±0.1	
		±0.2	
		±0.1	

DS

Changzhou Dragon State Electronic Co., Ltd

