



Ordering Information:

Circuit	Dimensions(mm)			
	A	B	C	D
02	2.00	13.00	16.00	7.00
03	4.00	15.00	18.00	9.00
04	6.00	17.00	20.00	11.00
05	8.00	19.00	22.00	13.00
06	10.00	21.00	24.00	15.00
07	12.00	23.00	26.00	17.00
08	14.00	25.00	28.00	19.00
09	16.00	27.00	30.00	21.00
10	18.00	29.00	32.00	23.00
11	20.00	31.00	34.00	25.00
12	22.00	33.00	36.00	27.00



SCALE: 1:1	UNIT: mm
SIZE: A4	
Unless otherwise General Tolerance:	
X	±0.50
X.x	±0.30
X.xx	±0.20
X°	±2°

Title: Horizontal Pitch2.0 Battery Conn DIP CH=3.25 C×5.0×H6.5mm			
Molde Code: GT-BTR200XX-0650A-002A			
DRAWN	CHECKED	APPROVED	DATE
Jiang	Xia	Chen	2023.12.28

品赞科技®
b-Switch
 www.dg-switch.com

REV: A0 SHEET: 1/1

GT-BT R 200 XX - 0650 A - 002A

G-Switch	Series BT: Battery	Type R: Receptacle	Pitch 200=2.00	Serial code	Detail A: With column B: No column	Height 0650=650	Pin Q' PY 02=2Pin 08=8Pin 03=3Pin 09=9Pin 04=4Pin 10=10Pin 05=5Pin 11=11Pin 06=6Pin 12=12Pin 07=7Pin
-----------------	------------------------------	------------------------------	--------------------------	--------------------	---	---------------------------	---

G-Switch Specification:

- Current rating: 5A
- Rated Voltage: 20V DC
- Insulation resistance: 100MΩ min
- Contact resistance: 30mΩ max
- Dielectric strength: 500V RMS
- Durability: 10,000cycles
- Operating temperature range: -40°C ~ +105°C

2	CONTACT	C5191	GF ON CONTACT AREA
1	HOUSING	PA9T	BLACK
NO.	PART NAME	MATERIAL	REMARK