

陶 瓷 電 容 器 Ceramic Disc Capacitor

Reference Specification

High Voltage Ceramic Capacitor HVC-10KV-DL15-F10-681K Issued Date: Dec 16,2023

Engineering Department **HVC Capacitor Manufacturing Co.,Ltd.**

▲ CAUTION

1. OPERATING VOLTAGE

When DC- rated capacitors are to be used in AC or ripple current circuits, be sure to maintain the Vp-p value of the applied voltage or the Vo-p which contains DC bias within the rated voltage range. When the voltage is started to apply to the circuit or it is stopped applying, the irregular voltage may be generated for a transit period because of resonance or switching. Be sure to use a capacitor within rated voltage containing these irregular voltage.



Excessive heat may lead to deterioration of the capacitor's characteristics and reliability.(Never attempt to perform measurement with the cooling fan running. Otherwise, accurate measurement cannot be ensured.)

3. OPERATING AND STORAGE ENVIRONMENT

The insulating coating of capacitors does not form a perfect seal; therefore, do not use or store capacitors in a corrosive atmosphere, especially where chloride gas, sulfide gas, acid, alkali, salt or the like are present. And avoid exposure to moisture. The capacitor is designed to be used in the insulating media, such as epoxy resin, silicone oil, etc.. There must be 3mm or more insulating media for each direction of the capacitor. In case of cleaning, bonding, or molding this product, verify that these processes do not affect product quality by testing the performance of a cleaned, bonded or molded product in the intended equipment. Store the capacitors where the temperature and relative humidity do not exceed -10 to 40 °C and 15 to 85 %. Use capacitors within 6 months after delivered.

4. VIBRATION AND IMPACT

Do not expose a capacitor or its leads to excessive shock or vibration during use.

5. SOLDERING

When soldering this product to a PCB/PWB, do not exceed the solder heat resistance specification of the capacitor. Subjecting this product to excessive heating could melt the internal junction solder and may result in thermal shocks that can crack the ceramic element.

When soldering capacitor with a soldering iron, it should be performed in following conditions.

Temperature of iron-tip : 400 °C max. Soldering iron wattage : 50W max. Soldering time : 3.5s max.

Failure to follow the above cautions may result, worst case, in a short circuit and cause fuming or partial dispersion when the product is used.

6. Limitation of Applications

Please contact us before using our products for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property.

①Aircraft equipment ②Aerospace equipment

Power plant control equipment

3Undersea equipment

SMedical equipment

©Transportation equipment(vehicles, trains, ships, etc.) ®Disaster prevention / crime prevention equipment

tc.) ⑦Traffic signal equipment ③Data-processing equipment

[®]Application of similar complexity and/or reliability requirements to the applications listed in the above.

NOTICE

Cleaning To perform ultrasonic cleaning, observe the following conditions. Rinse bath capacity : Output of 20 watts per liter or less. Rinsing time : 5min maximum. Do not vibrate the PCB/PWB directly. Excessive ultrasonic cleaning may lead to fatigue destruction of the lead wires.

Capacitance change of capacitor

Class 1 capacitors

Capacitance might change a little depending on a surrounding temperature or an applied voltage. Please contact us if you use for the strict time constant circuit.

Class 2 and 3 capacitors

Class 2 and 3 capacitors like temperature characteristic B, E and F have an aging characteristic, whereby the capacitor continually decreases its capacitance slightly if the capacitor leaves for a long time... Moreover, capacitance might change greatly depending on a surrounding temperature or an applied voltage. So, it is not likely to be able to use for the time constant circuit. Please contact us if you need a detail information.

▲ NOTE

- 1. Please make sure that your product has been evaluated in view of your specifications with our product being mounted to your product.
- 2. You are requested not to use our product deviating from the agreed specifications.

 Application This specification is applied to high voltage ceramic capacitor used for in high voltage electric equipment. 												
2. Rating 2.1 Operating temperature -35°C to +85°C												
2.2 Part unmber <u>HVC</u> <u>10KV</u> <u>DL</u> <u>15</u> <u>F</u> <u>10</u> <u>681</u> <u>K</u> Brand Rated Voltage N4700 Diameter(mm) Pitch Lead spacing Cap. Tol.												
Temperature characteristic Temperature characteristic N4700												
Rated voltage Rated voltage DC10kV												
 Capacitance The first two digits denote significant figures ; the last digit denotes the multiplier of 10 in pF. ex.) In case of 680. 												
68 X 10 ['] = 680 pF • Capacitance tolerance Please refer to [4. Part number list].												
Lead style Lead style Straight long												
Solder coated copper wire is applied for termination.												
Packing type Bulk												
 Individual specification In case part number cannot be identified without 'individual specification', it is added at the end of part number. 												



5.TEST 5-1VISUAL EXAMINATION CHECK OF DIMENSIONS

No.	ITE	Μ	SPECIFICATION	TESTING METHOD										
1	Appearance dim	ensions	Shall be visually examined or Venire											
				Calipers.										
2	Marking		Shall be vis	ually ex	amine	J.								
5-21	ELECTRICAL PER	RFORMANCE T	ESTS											
1	Dielectric Strength	Dielectric Between No failure Strength Lead wires					The capacitors shall not be damage when DC voltage of 150% of the rated voltage are applied between the lead wires for 60 s in insulate liquid or gas.							
		Body insulation		(Charge/discharge current: 50mA max.) The capacitors is placed in the container with metal balls of diameter 1mm so that each lead wires, Short-circuited, is kept approximately 2mm off the balls as shown in the figure, and DC voltage of 15kV is applied for 10 s between capacitor lead wires and small metals. (Charge/discharge current: 50mA max.)										
2	Insulation Resistance (I.R.)	Between Lead wires	200,000 MΩ min.	measured with DC 1kV within 60- charging.										
3	Capacitance		Within the specified tolerance.	The capacita 20°C with 7 max	measu AC5V(red at r.m.s.)								
4	Dissipation Factor (D.F.)		ation Factor 0.2% max.				tance.							
5	Temperature Cha	aracteristic	-4700ppm/ °C	The capacita made at each Capacitance 3 shall not ex Emp 1 N4700 -	easuren becified from the e limit sp 3 20+2°C	nent sh in table. e value o ecified. 4	of step							

5-3 MECHANICAL PERFORMANCE TESTS

No.	ITE	М	SPECIFICATION	TESTING METHOD					
1	Strength	Pull	Lead wire shall not cut off.	Fix the body of capacitor, apply a					
	of Lead		Capacitor shall not be	tensile weight gradually to each lead					
			broken.	wire in the radial direction of capacitor					
				up to 10N, and keep it for 10±1 s.					
		Bending		Each lead wire shall be subjected to 5N					
				weight and then a 90° to bend, at the point					
				of egress, in one direction, return to					
				original position, and then a 90° bend in					
				the opposite direction at the rate of one					
	0.11.1.11.1.1.1			bend in 2 to 3 s.					
2	Solderability of L	eads	Lead wire shall be soldered	The lead wire shall be dipped into a					
			with uniformly coated on the	25% methanol solution of rosin and					
			axial direction over 3/4 of the	then into molten solder of 235±5°C for					
			circumferential direction.	2±0.5 S.					
				In both cases the depth of dipping is up					
				to about 1.5 to 2.0mm from the root of					
	O a lata sina si	A	No se esta data data da	The lead wires.					
3	Soldering	Appearance	No marked defect.	The lead wires shall be immersed into					
	Effect	Capacitance	Within±10%	the melted solder of 350±10°C up to					
		Change		about 1.5 to 2.0mm from the main body					
		Dielectric	No failure	for 3.5±0.5 s.					
		Strength		Post-treatment: Capacitor shall be stored					
		(Between		for 24±2 h at room condition.					
		lead wires)							

HVCAP

HVC CAPACITOR MANUFACTURING CO., LTD 赫威斯电容器制作有限公司

公司简介

赫威斯电容器(HVC Capacitor)制作有限公司为港资企业,成立于 2012 年 1 月,为拥有 20 多年生产高压陶瓷产品台系厂商成立的出口运营品牌,生产基地位于东莞虎门,产品 95%出口。

赫威斯电容器专业生产高压陶瓷电容, 蓝色陶瓷片型和螺栓型陶瓷电容, 其中陶瓷片电容电压做 到 2KV 到 50KV, 拥有 独特专利的 N4700 军工级别陶瓷介电材质 (N4700 材质 6KV 到 40KV), 主要应用在高端医疗电子设备, 如 CT, 医疗 X 光机, C 型臂, DR 机, 牙医 X 光机, 机场安检, 无损检测,静电除尘设备等等。螺栓型陶瓷片电容主打 N4700 材质,电压范围 10KV 到 150KV, 外形为黑色环氧树脂包封。主要客户为通用电气, 柯尼卡美能达, 日立 ABB, 尼康, 西门子, 美 国强生,美国贝克休斯等知名 500 强企业和众多纳斯达克上市医疗设备公司。

用中国产军工级别材质生产达到外国高端工业水准的电子零件,是赫威斯公司的经营方针和一贯追求。2017 年起至今,美日欧品牌如日本**村田**,美国 AVX,美国威世纷纷由于商业考量和疫情原因退出市场造成供需缺口,赫威斯电容很好地承接了国际高压设备客户的需求。2018 年起赫威斯公司采用收购和合作方式,建立高压电容相搭配的高压二极管和高压厚膜电阻产品线,也逐渐获得高压设备客户的认可。

赫威斯公司现有国外代理商伙伴分布在德国、法国、英国、美国、日本、韩国、印度、俄罗斯。 为应对中国市场外资工厂的需求,也设立了中国代理商,国内外代理商主要由赫威斯公司指派跟 进当地重点客户。我司的目标是成为高压电子零件行业知名的新兴品牌。

HVC Capacitor is HongKong owned manufacturing company, with over 20 years production experience in high voltage ceramic capacitors field. Our plant located in Dongguan City, Southern China. Currently, 95% of HVC product are exported, HVC capacitor also has significant present in domestic market.

HVC Capacitor specializes in producing both lead type ceramic disc capacitors (blue color) and screw terminal type ceramic capacitors(black resin). For ceramic disc type available voltage from 2KV to 50KV (patent N4700 material) Typical applications including Medical X-ray machines, C-arm, DR(digital radiography), Dental X-ray, Security scanner, NDT(Industrial Non-destructive testing), electrostatic precipitator, and negative lon machines etc.For screw terminal caps, HVC Capacitor also using N4700 ceramic dielectric, available voltage ranging from 10KV to 150KV. Key customers include GE Healthcare (General Electric), Konica Minolta, Hitachi ABB, Nikon, Siemens, Johnson & Johnson, Baker Hughes, and other Fortune 500 companies. HVC Capacitor's screw terminal products has approved by numbers of NASDAQ-listed medial machine companies.

HVC using Chinese military-grade ceramic dielectric to build capacitor, to meet foreign high end industrial quality demands. Since 2017, HVC Capacitor has successfully replaced Japanese **Murata** and American **Vishay** and **AVX**, who facing obsoleted and supplement and costing problem. HVC Capacitor also builds own brand high voltage diodes(HVD series) and high voltage thick film resistors(HVR series) to meet customer complementary requirements. HV diodes matching up with high voltage ceramic capacitor to build up voltage multiplier circuit, which is essential for high voltage power supply. HVC's HVD series diode has already been approved by important European, USA, and Japanese end user.

HVC Capacitor has established an international distribution channel in advance industrial countries, such as Germany, France, U.K., U.S.A, Japan, Korea, India, and Russia. In U.S. market, HVC cooperates with global top electronic component distributors like **AVNET**, **Digi-Key**, **Bisco Industries**, **IBS electronics**. HVC also signed up two Chinese domestic distributors to handle requirement from local EMS/OEM.

HVC Capacitor strive to be well-known emerging brand in high voltage component industry.



HVC CAPACITOR MANUFACTURING CO., LTD 赫威斯电容器制作有限公司

INTERNATIONAL DISTRIBUTION

CHINA

SUZHOU SUNLIT ELECTRONIC CO.,LTD

★ * **

苏州工业园区通园路398号海逸大厦A401 TEL:(+86)-512-6288-4061 FAX:(+86)-512-6288-4062 CONTACT:Mr.David Liu EMAIL:Dsq@sz-sunlit.com







KOREA BLUE & GREEN TRADING CO.,LTD. Room#A-512B Woolim Lion's Valley 371-28 Gasan-dong,Gumchun-gu,Seoul, Korea TEL:(+82) 2 2026 4440 FAX:(+82) 2 2026 4443 CONTACT:Ms.Chang Mee EMAIL: chang@BlueAndGreen.co.kr

GERMANY AMEC GmbH Langer Acker 32, 30900 Wedemark,Germany TEL: (+49) (5130) 58642-22 FAX: (+49 (5130) 58642-10 CONTACT:Mr.Marcel Fehrmann EMAIL: Marcel.Fehrmann@amec-gmbh.de

JAPAN

名古屋理研電具株式会社 愛知県名古屋市昭和区檀渓通1-20 〒466-0842 TEL: (+81) 052-833-1248 FAX: (+81) 052-833-2640 連絡先: Mr. 古田 EMAIL:furuta@nagoya-riken.co.jp



ETRONICS 8,rue Temara B.P. 80875 78100 Saint Germain en Laye,France TEL : (+33) 01.39.10.29.00 MOB: (+33) 06.42.20.44.43 CONTACT:Mr.Hampton RUCKLI EMAIL: hampton.ruckli@etronics.fr



UK ASHLEA COMPONENTS LTD. Technology House Unit 24a, Shrivenham Hundred Business Park Watchfield Swindon SN6 8TZ ,UK. TEL: (+44)(0)1793 786027 FAX: (+44)(0)1793 783646 CONTACT:Ms. Emma Packford-Garrett EMAIL: Emma.Packford-Garrett@ashlea.co.uk



U.S.A BISCO INDUSTRIES 1328 Blue Oaks Blvd Ste 120 Roseville, CA 95678, U.S.A TEL:(+1)-916-773-1634 FAX:(+1)-714-876-2493 CONTACT:Mr.Tom Allan EMAIL: tallan@biscoind.com

IBS ELECTRONIC, INC 3506D West Lake Center Drive Santa Ana, CA 92704 United States Tel: (+1)-800-717-6475 Fax: (+1)-800-824-7668 CONTACT:Sales Team EMAIL:simon@ibselectronics.com

MIRA KONDENSATOREN GmbH Weilemer Weg 35, 71155 Altdorf, Germany TEL:(+49) (0) 70 31 – 70 29 91 – 9 FAX:(+49) (0) 70 31 – 70 29 91 – 5 CONTACT:Ms.Andrea Fonas / Mr.Thomas Gampe EMAIL: a.fonas@mira-kondensatoren.de



APPLICATION

Electrostatic Spraying Equipment



Negative Ion Generator



Welding Equipment



Medical Equipment(CT)





Tesla Coil





Power Electronic Equipment





HVC CAPACITOR MANUFACTURING CO., LTD 赫威斯电容器制作有限公司

KEY CLIENTS

HVCAP





Ceramic Disc Style

Ceramic Disc Capacitors Class 1 and 2, 1 kV_{DC} to 50 kV_{DC} , General Purpose



Capacitors with 7.5 mm (0.30") to 15 mm (0.40") lead spacing(P)

QUICK REFERENCE DATA									
DESCRIPTION	UJ,SL,X5F,X7R,N4700,Y5T,Y5U,Y5V								
Voltage (V _{DC})	1000 to 50000								
Min. Capacitance (pF)	10								
Max. Capacitance (pF)	33 000								
Mounting	Through hole								

OPERATING TEMPERATURE RANGE

Class 1: SL, - 40 °C to + 85 °C Class 1: N4700, - 25 °C to + 100 °C Class 2: Y5T, Y5U, Y5V, - 25 °C to + 85 °C Class 2: X7R, - 40 °C to + 125 °C

TEMPERATURE COEFFICIENTS

Class 1 SL, N4700 Class 2 X7R, Y5P, Y5T, Y5V, X5F,Y5U

CAPACITANCE RANGE

10 pF to 33 000 pF

RATED DC VOLTAGE

1 kV to 50 kV

DIELECTRIC STRENGTH

150 % of rated voltage (10 kV to 50 kV)

FEATURES

- Low losses
- High stability
- High capacitance in small size
- Kinked (preferred) or straight leads
- Compliant to RoHS directive 2002/95/EC

APPLICATIONS

- DC high voltage
- Pulse high voltage
- SMPS
- HV power supply
- HF ballast

DESIGN

The capacitors consist of a ceramic disc both sides of which are silver-plated. Connection leads are made of tinned copper.

The capacitors may be supplied with kinked or straight leads with a lead spacing of 5 mm (0.20"), 7.5 mm (0.30") or 10 mm (0.40") and a lead length from 4 mm to 30 mm. The standard tolerance on capacitance is 5 % or 10 % for class 1 capacitors and \pm 10 % or \pm 20 % for class 2 capacitors. Encapsulation is made of blue-colored epoxyresin.

INSULATION RESISTANCE AT 500 V_{DC}

 N4700:
 >= 200 000 MΩ

 UJ,SL,X5F,X7R,Y5T:
 >= 100 000 MΩ

 Y5U,Y5V:
 >= 10 000 MΩ

TOLERANCE ON CAPACITANCE

± 5 %; ± 10 %; ± 20 %; + 80/- 20 % Other tolerances available on request

DISSIPATION FACTOR

UJ,SL: 6X10⁻⁴ X5F: 1% X7R: 1.5% N4700: 0.2% Y5T: 1% Y5U,Y5V: 2%





Ceramic Disc Style

Ceramic Disc Capacitors Class 1 and 2, 1 kV_{DC} to 50 kV_{DC}, General Purpose

N0.	Part Number	Material	aterial Max (mr		(mm)		N0.	Part Number	Material		Max	x (mm)		
			D	Т	Р	d				D	Т	Р	d	
1	HVC-2KV-N08-F7.5-10PK	NP0	8	4	7.5	0.6	47	HVC-3KV-DP14-F10-472K	Y5P	14	4.5	10	0.6	
2	HVC-2KV-N08-F7.5-15PK	NP0	8	4	7.5	0.6	48	HVC-3KV-E10-F10-472M	Y5U	10	4.5	10	0.6	
3	HVC-2KV-SL08-F7.5-22PK	SL	8	4	7.5	0.6	49	HVC-3KV-E17-F10-103M	Y5U	17	4.5	10	0.65	
4	HVC81-2KV-SL08-F7.5-27PK	SL	8	4	7.5	0.6	50	HVC-3KV-F11-F10-103M	Y5V	11	4.5	10	0.6	
5	HVC-2KV-SL08-F7.5-33PK	SL	8	4	7.5	0.6	51	HVC-6KV-N09-F10-10PK	NP0	9	6	10	0.6	
6	HVC-2KV-SL08-F7.5-47PK	SL	8	4	7.5	0.6	52	HVC-6KV-SL08-F10-10PK	SL	8	5	10	0.6	
7	HVC-2KV-SL08-F7.5-56PK	SL	8	4	7.5	0.6	53	HVC-6KV-SL08-F10-22PK	SL	8	5	10	0.6	
8	HVC-2KV-SL08-F5-68PK	SL	8	4	7.5	0.6	54	HVC-6KV-SL08-F10-33PK	SL	8	5	10	0.6	
9	HVC-2KV-DP08-F5-101K	Y5P	8	4	7.5	0.6	55	HVC-6KV-SL08-F10-47PK	SL	9	5	10	0.6	
10	HVC-2KV-DP08-F7.5-151K	Y5P	8	4	7.5	0.6	56	HVC-6KV-SL09-F10-101K	SL	9	6	10	0.6	
11	HVC-2KV-DP08-F7.5-221K	Y5P	8	4	7.5	0.6	57	HVC-6KV-DL06-F5-101K	N4700	6	4	5	0.5	
12	HVC-2KV-DP08-F7.5-331K	Y5P	8	4	7.5	0.6	58	HVC-6KV-DP09-F10-101K	Y5P	9	5	10	0.6	
13	HVC-2KV-DP08-F7.5-471K	Y5P	8	4	7.5	0.6	59	HVC-6KV-DP09-F10-221K	Y5P	9	5	10	0.6	
14	HVC-2KV-DP08-F7.5-561K	Y5P	8	4	7.5	0.6	60	HVC-6KV-DL08-F10-221K	N4700	10	6	10	0.6	
15	HVC-2KV-DP08-F7.5-681K	Y5P	8	4	7.5	0.6	61	HVC-6KV-DP09-F10-331K	Y5P	9	5	10	0.6	
16	HVC-2KV-DP08-F7.5-102K	Y5P	8	4	7.5	0.6	62	HVC-6KV-DL10-F10-331K	N4700	10	5	10	0.6	
17	HVC-2KV-DP08-F10-222K	Y5P	8	4	10	0.6	63	HVC-6KV-DP09-F10-471K	Y5P	9	5	10	0.6	
18	HVC-2KV-E07-F7.5-222M	Y5U	7	4	7.5	0.6	64	HVC-6KV-DL11-F10-471K	N4700	11	5	10	0.6	
19	HVC-2KV-DP14-F10-332K	Y5P	14	4	10	0.6	65	HVC-6KV-DP11-F10-102K	Y5P	11	5	10	0.6	
20	HVC-2KV-E11-F10-332M	Y5U	11	4	10	0.6	66	HVC-6KV-D11-F10-102K	Y5T	11	6	10	0.6	
21	HVC-2KV-DP14-F10-472K	Y5P	14	4	10	0.6	67	HVC-6KV-E08-F10-102M	Y5U	8	5	10	0.6	
22	HVC-2KV-E11-F10-472M	Y5U	11	4	10	0.6	68	HVC-6KV-D16-F10-222K	Y5T	16	5	10	0.6	
23	HVC-2KV-DP17-F10-103K	Y5P	17	4	10	0.8	69	HVC-6KV-E10-F10-222M	Y5U	10	5	10	0.6	
24	HVC-2KV-E14-F10-103M	Y5U	14	4	10	0.6	70	HVC-6KV-DL08-F10-221K	N4700	8	6	10	0.6	
25	HVC-2KV-F09-F10-103Z	Y5V	9	4	10	0.6	71	HVC-6KV-DL14-F10-102K	N4700	14	6	10	0.6	
26	HVC-3KV-SL08-F7.5-10PK	SL	8	4.5	7.5	0.6	72	HVC-6KV-DL10-F10-471K	N4700	10	6	10	0.6	
27	HVC-3KV-SL08-F7.5-15PK	SL	8	4.5	7.5	0.6	73	HVC-6KV-E15-F10-332M	Y5U	15	5	10	0.6	
28	HVC-3KV-SL08-F7.5-22PK	SL	8	4.5	7.5	0.6	74	HVC-6KV-E17-F10-472M	Y5U	17	5	10	0.6	
29	HVC-3KV-SL08-F7.5-27PK	SL	8	4.5	7.5	0.6	75	HVC-6KV-E23-F12.5-103M	Y5U	23	6	12.5	0.8	
30	HVC-3KV-SL08-F7.5-33PK	SL	8	4.5	7.5	0.6	76	HVC-6KV-F19-F9.5-103M	Y5V	19	6	10	0.65	
31	HVC-3KV-SL08-F7.5-47PK	SL	8	4.5	7.5	0.6	77	HVC-10KV-D06-F7.5-101K	Y5T	6	5	7.5	0.65	
32	HVC-3KV-SL08-F7.5-56PK	SL	8	4.5	7.5	0.6	78	HVC-10KV-DL07-F10-101K	N4700	7	7	10	0.65	
33	HVC-3KV-SL08-F7.5-68PK	SL	8	4.5	7.5	0.6	79	HVC-10KV-D08-F7.5-151K	Y5T	7	6	7.5	0.65	
34	HVC-3KV-SL08-F7.5-101K	SL	8	4.5	7.5	0.6	80	HVC-10KV-DL08-F10-151K	N4700	8	7	10	0.65	
35	HVC-3KV-DP06-F5-101K	Y5P	6	4	5	0.6	81	HVC-10KV-D08-F7.5-221K	Y5T	8	5.5	7.5	0.65	
36	HVC-3KV-DP08-F10-151K	Y5P	8	4.5	10	0.6	82	HVC-10KV-DL08-F10-221K	UJ	9	5	9.5	0.6	
37	HVC-3KV-DP08-F10-221K	Y5P	8	4.5	10	0.6	83	HVC-10KV-D08-F7.5-331K	Y5T	8	6	7.5	0.65	
38	HVC-3KV-DP08-F10-331K	Y5P	8	4.5	10	0.6	84	HVC-10KV-DL08-F10-331K	N4700	10	6.5	10	0.65	
39	HVC-3KV-DP08-F10-471K	Y5P	8	4.5	10	0.6	85	HVC-10KV-D09-F10-471K	Y5T	9	6	10	0.65	
40	HVC-3KV-DP08-F10-561K	Y5P	8	4.5	10	0.6	86	HVC-10KV-DL12-F10-471K	N4700	12	7	10	0.8	
41	HVC-3KV-DP08-F10-681K	Y5P	8	4.5	10	0.6	87	HVC-10KV-D10-F10-681K	Y5T	10	6	10	0.65	
42	HVC-3KV-DP08-F10-102K	Y5P	8	4.5	10	0.6	88	HVC-10KV-DL15-F10-681K	N4700	15	7	10	0.8	
43	HVC-3KV-DP10-F10-222K	Y5P	10	4.5	10	0.6	89	HVC-10KV-D14-F10-102K	Y5T	14	7	10	0.8	
44	HVC-3KV-E08-F10-222M	Y5U	8	4.5	10	0.6	90	HVC-10KV-DL16-F10-102K	N4700	16	7	10	0.8	
45	HVC-3KV-DP14-F10-332K	Y5P	10	14	4.5	0.6	91	HVC-10KV-D17-F10-222K	Y5T	17	7	10	0.8	
46	HVC-3KV-E08-F5-332M	Y5U	8	4.5	5	0.6	92	HVC-10KV-E14-F10-222M	Y5U	14	7	10	0.8	



Ceramic Disc Capacitors Class 1 and 2, 1 kV_{DC} to 50 kV_{DC} , General Purpose

NO.	Part Number	Material	rial N		Max (mm)				N0.	PartNumber	Material	Max (mm)				
			D	Т	Р	d	t				D	т	Р	d		
93	HVC-10KV-D21-F12.5-332K	Y5T	21	7	12.5	0.8	Ī	141	HVC-20KV-F20-F12.5-682Z	Y5V	20	9	12.5	0.8		
94	HVC-10KV-E16-F10-332M	Y5U	16	7	10	0.8	Ī	142	HVC-20KV-F24-F12.5-103Z	Y5V	40	22	20	1.2		
95	HVC-10KV-E20-F12.5-472M	Y5U	20	7	12.5	0.8	Ī	143	HVC-25KV-D09-F7.5-221K	Y5T	9	8.5	7.5	0.65		
96	HVC-10KV-F17-F12.5-682Z	Y5V	17	8	12.5	0.8	Ī	144	HVC-25KV-D10-F10-331K	Y5T	10	8.5	10	0.65		
97	HVC-10KV-E33-F20-103M	Y5U	33	9	20	0.8	1	145	HVC-25KV-D11-F10-471K	Y5T	11	8.5	10	0.65		
98	HVC-10KV-F21-F12.5-103Z	Y5V	21	7	12.5	0.8	I.	146	HVC-25KV-D13-F10-681K	Y5T	13	9	10	0.65		
99	HVC-10KV-D21-F12.5-332M	Y5T	24	8.5	12.5	0.8		147	HVC-25KV-D16-F12.5-102K	Y5T	16	9	12.5	0.8		
100	HVC-15KV-D07-F7.5-101K	Y5T	7	7	7.5	0.65	I.	148	HVC-25KV-D22-F12.5-222K	Y5T	22	10	12.5	0.8		
101	HVC-15KV-DL07-F10-101K	N4700	7	7	10	0.65		149	HVC-25KV-F17-F12.5-472Z	Y5V	17	9	12.5	0.8		
102	HVC-15KV-DL09-F10-151K	N4700	9	7	10	0.65	I	150	HVC-25KV-F25-F16-103Z	Y5V	25	10.5	16	0.8		
103	HVC-15KV-D08-F7.5-221K	Y5T	8	7	7.5	0.65		151	HVC-30KV-D08-F10-101K	Y5T	8	9	10	0.65		
104	HVC-15KV-DL10-F10-221K	N4700	10	7	10	0.65		152	HVC-30KV-DL10-F10-101K	N4700	10	10	10	0.8		
105	HVC-15KV-D08-F7.5-331K	Y5T	8	7	7.5	0.65		153	HVC-30KV-D10-F15-151K	Y5T	10	11	15	0.8		
106	HVC-15KV-DL12-F10-331K	N4700	12	8	10	0.65	Ι	154	HVC-30KV-DL10-F10-151K	N4700	10	9	10	0.8		
107	HVC-15KV-D09-F10-471K	Y5T	9	7	10	0.65	Ι	155	HVC-30KV-D11-F15-221K	Y5T	11	11	15	0.8		
108	HVC-15KV-DL14-F10-471K	N4700	14	8	10	0.8		156	HVC-30KV-DL13-F12.5-221K	N4700	13	9	12.5	0.8		
109	HVC-15KV-D11-F10-681K	Y5T	11	7	10	0.65	Ī	157	HVC-30KV-D11-F10-331K	Y5T	11	10	10	0.8		
110	HVC-15KV-DL16-F10-681K	N4700	16	8	12.5	0.8	Ī	158	HVC-30KV-DL15-F10-331K	N4700	15	11	10	0.8		
111	HVC-15KV-D13-F10-102K	Y5T	13	7	10	0.8	t i	159	HVC-30KV-D12-F12.5-471K	Y5T	12	10	12.5	0.8		
112	HVC-15KV-DL18-F12.5-102K	N4700	18	8	12.5	0.8	1	160	HVC-30KV-DL20-F12.5-471K	N4700	20	11	12.5	0.8		
113	HVC-15KV-D19-F12.5-222K	Y5T	19	8	12.5	0.8	1	161	HVC-30KV-DL20-F12.5-501K	N4700	20	12	16	0.8		
114	HVC-15KV-DL26-F12.5-202K	N4700	26	8	12.5	0.8	1	162	HVC-30KV-DL19-F17.5-501K	N4700	19	11	17.5	0.8		
115	HVC-15KV-DL26-F12.5-222K	N4700	26	10	12.5	0.8	1	163	HVC-30KV-D14-F12.5-681K	Y5T	14	10	12.5	0.8		
116	HVC-15KV-E21-F12.5-472M	Y5U	21	7	12.5	0.8	1	164	HVC-30KV-D17-F12.5-102K	Y5T	17	10.5	12.5	0.8		
117	HVC-15KV-F18-F12.5-682Z	Y5V	18	8	12.5	0.8	Ī	165	HVC-30KV-DL28-F17.5-102K	N4700	28	15	17.5	1.0		
118	HVC-15KV-F23-F12.5-103Z	Y5V	23	8	12.5	0.8	1	166	HVC-30KV-D24-F14-222K	Y5T	24	10.5	14	1.0		
119	HVC-20KV-D07-F7.5-101K	Y5T	7	8	7.5	0.65		167	HVC-30KV-D26-F18-222K	Y5T	26	13	18	1.0		
120	HVC-20KV-DL08-F10-101K	N4700	8	8	10	0.65		168	HVC-30KV-E23-F13-332M	Y5U	23	13	13	0.8		
121	HVC-20KV-DL11-F10-151K	N4700	11	8	10	0.65	I	169	HVC-30KV-F23-F15-472Z	Y5V	23	13	15	0.8		
122	HVC-20KV-D07-F7.5-221K	Y5T	7	7	7.5	0.65		170	HVC-30KV-F28-F16-103Z	Y5V	28	12	16	0.8		
123	HVC-20KV-DL12-F10-221K	N4700	12	8	10	0.65	I	171	HVC-30KV-F31-F16-103Z	Y5V	31	15	16	0.8		
124	HVC-20KV-D09-F7.5-331K	Y5T	9	7	7.5	0.65	Ι	172	HVC-40KV-D08-F10-101K	Y5T	8	12	10	0.8		
125	HVC-20KV-DL13-F10-331K	N4700	13	9	10	0.65		173	HVC-40KV-DL11-F10-101K	N4700	11	12	10	0.8		
126	HVC-20KV-D11-F10-471K	Y5T	11	8	10	0.65		174	HVC-40KV-DL16-F12.5-221K	N4700	16	13	12.5	0.8		
127	HVC-20KV-DL16-F10-471K	N4700	16	9	10	0.8		175	HVC-40KV-D10-F10-251K	Y5T	10	12	12.5	0.8		
128	HVC-20KV-D12-F10-501K	Y5T	12	8	10	0.65		176	HVC-40KV-D15-F15-471K	Y5T	15	13.5	15	0.8		
129	HVC-20KV-D13-F10-681K	Y5T	13	8.5	10	0.65		177	HVC-40KV-DL25-F16-501K	N4700	25	17	16	1.0		
130	HVC-20KV-D15-F10-102K	Y5T	15	8.5	10	0.8	Ι	178	HVC-40KV-D19-F14-102K	Y5T	19	13	14	0.8		
131	HVC-20KV-D17-F12.5-102K	Y5T	17	9	12.5	0.8	Ι	179	HVC-40KV-DL32-F20-102K K	N4700	32	16	20	1.2		
132	HVC-20KV-D20-F12.5-102K	Y5T	20	8	12.5	0.8	Ι	180	HVC-50KV-SL15-F12.5-22PK	SL	15	17	12.5	0.8		
133	HVC-20KV-E12-F10-102K	Y5U	12	8	10	0.65	I	181	HVC-50KV-SL16-F12.5-50P	SL	16	17	12.5	0.8		
134	HVC-20KV-DL21-F12.5-102K	N4700	21	10	12.5	0.8	l	182	HVC-50KV-DL12-F10-101K	N4700	12	13	12.5	0.8		
135	HVC-20KV-DL28-F16-202K	N4700	28	10	16	0.8	Ι	183	HVC-50KV-D11-F16-251K	Y5T	11	14	16	0.8		
136	HVC-20KV-DL28-F16-222K	N4700	28	10	16	0.8	Ī	184	HVC-50KV-D16-F16-471K	Y5T	16	16	16	0.8		
137	HVC-20KV-D18-F10-152K	Y5T	18	8.5	10	0.8	Ī	185	HVC-50KV-DL27-F16-501K	N4700	27	19	16	1.2		
138	HVC-20KV-D21-F12.5-222K	Y5T	21	8.5	12.5	0.8	Ī	186	HVC-50KV-D22-F16-102K	Y5T	22	18	16	0.8		
139	HVC-20KV-E21-F12.5-332M	Y5U	21	8.5	12.5	0.8	Ī	187	HVC-50KV-DL34-F18-102K	N4700	34	19	18	1.2		
140	HVC-20KV-E23-F12.5-472M	Y5U	23	8.5	12.5	0.8	I	188	HVC-50KV-E26-F20-222M	Y5U	26	19	20	1.2		