

客户承认书

SPECIFICATION FOR APPROVAL

CUSTOMER/客户: _____

CUSTOMER P.N./客户物料号: _____

MODEL NO./产品型号: _____ **YSG-350-24** _____

PRODUCT NO./产品编号: _____ **350W 24V/14.6A 无风扇** _____

SAMPLE DATE/送样日期: _____ **2021-7-29** _____

| CUSTOMER AUTHORIZED SIGNATURE/客户承认签核 | | |
|--------------------------------------|--|--|
| | | |

Please return to us one copy of "SPECIFICATION FOR APPROVAL" with you approved signature./客户确认签字，盖章后请回传一份承认书给我司。

| | | | |
|-----|--------|--------|-----|
| 拟制: | 安规工程师: | 项目工程师: | 批准: |
| | | | |

**** Table Of Content/目录 ****

| | |
|--|---|
| 1. Functional description/功能描述..... | 3 |
| 2. SCOPE/简述..... | 3 |
| 2.1. Description/产品类型..... | 3 |
| 3. Input Characteristics/输入特性 | 3 |
| 3.1. Input Voltage & Frequency/输入电压与频率 | 3 |
| 3.2. Input AC Current/AC 输入电流..... | 3 |
| 3.3. Inrush Current (cold start)/浪涌电流(冷启动)..... | 4 |
| 3.4. Type Efficiency/典型效率..... | 4 |
| 3.5. Energy Consumption /空载功耗 | 4 |
| 4. Output Characteristics/输出特性..... | 4 |
| 4.1. Static Output Characteristics <Vo & R+N>/静态输出特性 | 4 |
| 4.2. Line/ Load Regulation/线性/负载调整率 | 4 |
| 4.3. Turn - on Delay Time/开机延迟时间 | 4 |
| 4.4. Hold-up Time/关机维持时间..... | 4 |
| 4.5. Rise Time/上升时间..... | 4 |
| 4.6. Fall Time/下降时间..... | 4 |
| 4.7. Output Overshoot / Undershoot/输出过冲/欠冲..... | 4 |
| 4.8. Output Load Transient Response/输出负载瞬态响应..... | 5 |
| 5. Protection Requirements/保护要求..... | 5 |
| 5.1. Over Current Protection/过流保护..... | 5 |
| 5.2. Short Circuit Protection/短路保护 | 5 |
| 5.3. Over Voltage Protection/过压保护 | 5 |
| 5.4. Over temperature protection/过温保护 | 5 |
| 6. Environment Requirements/环境要求 | 5 |
| 6.1. Operating Temperature and Relative Humidity/操作温/湿度要求..... | 5 |
| 6.2. Storage Temperature and Relative Humidity/存储温/湿度要求 | 5 |
| Sea level shall be low 2.000 meters/低于 2000 | |
| 6.3. 米. | 5 |
| 6.4. Vibration/振动 | 5 |
| 7. Reliability Requirements/可靠性要求 | 6 |
| 7.1. Burn-in/老化 | 6 |
| 7.2. E-caps lifetime | 7 |
| 7.3. MTBF : | 7 |
| 8. EMI/EMS Standards/EMI/EMS 标准 | 7 |
| 8.1. EMI Standards/EMI 标准 | 7 |
| 8.2. EMS Standards/EMS 标准 | 8 |
| 9. Safety Standards/安规标准 | 8 |
| 10. Mechanical Outline Drawing/外观示意图 | 9 |

1. Functional description/功能描述

YSG-350-24 is a 350W output closed-type power supply with a 30mm thin design and a wide input voltage range of 90 ~ 264Vac. The output voltage is single channel 24V, and the peak efficiency is as high as 93%. It is designed with an aluminum casing for good heat dissipation. The power supply has a variety of protection functions, such as input under-voltage protection, output over-current protection, output over-voltage protection and temperature protection. It conforms to the harmonics requirement of EN 61000-3-2. It provides a high performance and cost-effective solution for various engineering applications.

YSG-350-24 是一款 350W 24V 输出封闭型电源供应器，具有 30mm 薄外型设计，**无风扇**，拨码切换宽输入电压范围 **90~264Vac**。输出电压为 24V，峰值**效率高达 94%**；采用铝外壳设计且具有很好的散热效果。该电源具有多种保护功能，如输入欠压保护、输出过流保护、输出过压保护、**输出短路锁死保护功能**；符合 **EN61000-3-2** 谐波要求；为各种工程应用提供了一个高性能和高性价比的解决方案。

2. SCOPE/简述

The document details the electrical, mechanical and environmental specifications of a SMPS, the power supply provides 350W continuous output power.

资料详细描述了一款 **350W** (连续输出功率)开关电源的电气性、结构性及环境等要求。

The power supply shall meet the **RoHS** requirement.

此款电源符合 **RoHS** 要求。

2.1. Description/产品类型

SMPS Adaptor(Wall mount)/插墙式适配器

SMPS Adaptor(Desk-top)/桌面型适配器

Open Frame/开放式结构

SMPS Unit (With Case)/带铝壳型

Others/其他

3. Input Characteristics/输入特性

3.1. Input Voltage & Frequency/输入电压与频率

The range of input voltage is from 90Vac to 264Vac single phase, switching the input voltage through a switch.

输入电压范围：从 **90Vac** 到 **264Vac**，单相输入，通过开关切换输入电压。

| Items | Min/最小 | Nom/额定值 | Max/最大 |
|----------------------|--------|-------------|---------|
| Input Voltage/输入电压 | 90 Vac | 100~240 Vac | 264 Vac |
| Input Frequency/输入频率 | 47 Hz | 50~60 Hz | 63 Hz |

3.2. Input AC Current/AC 输入电流

| | | | |
|--------------------------|----------|--------|-----------|
| Input Voltage/输入电压 | 115Vac | 230Vac | Full load |
| Input AC Current/AC 输入电流 | 5.5A Max | 3A Max | Full load |

3.3. Inrush Current (cold start)/浪涌电流(冷启动)

The energy of inrush current should not be over the I^2T of fuse & bridge diodes.

冷启动时，浪涌能量不能超过整流桥和保险丝的 I^2T ，且不能有损坏。

3.4. Type Efficiency/典型效率

91% min.(average efficiency). @115Vac/60Hz input .

94% min.(average efficiency).@230Vac/50Hz input.

输入电压 115V/60Hz 时，平均效率不低于 91%。

输入电压 230V/50Hz 时，平均效率不低于 94%。

3.5. Energy Consumption /空载功耗

No load Consumption $\leq 0.7W$ (230Vac/50Hz).

在额定输入 230Vac/50Hz 时,空载功耗 $\leq 0.7W$ 。

4. Output Characteristics/输出特性

4.1. Static Output Characteristics <Vo & R+N>/静态输出特性

| Output | Rated Load/额定负载 | | Output Range | R+N | Remark |
|--------|-----------------|-----------|---------------|----------|--------|
| Rate | Min. Load | Rate.Load | 输出电压范围 | 纹波与噪声 | 备注 |
| +24V | 0.0A | 14.6A | 22.8V ~ 25.2V | 200mVp-p | |

Ripple & Noise: Measurement is done by 20MHz bandwidth oscilloscope and the output paralleled a 0.1uF ceramic capacitor and a 10uF electrolytic capacitor. (test under the condition of rated input and rated output).

纹波与噪声：量测时示波器选用 20MHz 带宽限制,输出端要并联一颗 0.1uF 的陶瓷电容和一颗 10uF 的电解电容. (在额定输入及输出的条件下检测) 。

4.2. Line/ Load Regulation/线性/负载调整率

| Output | Load Condition/负载条件 | | Line Regulation | Load Regulation | Remark |
|--------|---------------------|-----------|-----------------|-----------------|--------|
| Rate | Min. Load | Rate.Load | 线性调整率 | 负载调整率 | 备注 |
| + 24V | 0.0A | 14.6A | $\pm 3\%$ | $\pm 3\%$ | |

4.3. Turn - on Delay Time/开机延迟时间

3S max. @115Vac to 230Vac input & Full load.

输入电压 115Vac to 230Vac 满载时，开机延迟时间不超过 3S。

4.4. Hold-up Time/关机维持时间

10mS min. @ Full load &115Vac/60Hz input turn off at worst case.

输入电压 115Vac/60Hz 满载时，关机时间最差情况不小于 10 毫秒。

10mS min. @ Full load &230Vac/50Hz input turn off at worst case.

输入电压 230Vac/50Hz 满载时，关机时间最差情况不小于 10 毫秒。

4.5. Rise Time/上升时间

80 mS max. @ Full load &115Vac/60Hz and 230Vac/50Hz input.

在 115Vac/60Hz 和 230Vac/50Hz 输入满载时，上升时间不超过 80 毫秒。

4.6. Fall Time/下降时间

30 mS max. @ Full load.

满载时，下降时间不超过 30 毫秒。

4.7. Output Overshoot / Undershoot/输出过冲/欠冲

10 % max. When the power on or off, when it is the full input voltage and full load.

开关机时，输出过冲/欠冲均不大于 10%。

4.8. Output Load Transient Response/输出负载瞬态响应

Output voltage within 22.8~25.2V for load step from 25% to 50% to 25%,50% to 75% to 50% R/S: 0.25A/uS, Transient Response Recovery Time :200uS, Dynamic response overshoot 10%.

输出电压在 22.8~25.2 V 之间,负载变化: 从 25% to 50% to 25%, 50% to 75% to 50%斜率: 0.25A/uS, 动态响应恢复时间: 20mS, 动态响应过冲±10%。

5. Protection Requirements/保护要求

5.1. Over Current Protection/过流保护

Over Power Point Limited: 105%~150% Full load (@115/230Vac)

过流保护点限制:105%~150% 满载 (115~230Vac)

The output shall hiccup when the over current applied to the output rail, and shall be self-recovery when the fault condition is removed.

当过流作用于输出时, 输出将锁死, 当故障情况消除时, 重新启动恢复。

5.2. Short Circuit Protection/短路保护

The input power shall decrease when the output short.the power supply shall no damage, and shall be auto-recovery when the fault condition is removed.

当输出短路时, 输入功率应减小。电源不应损坏, 故障排除后重新启动恢复。

5.3. Over Voltage Protection/过压保护

In the case of 90 ~ 264Vac input space time load and full load,22V < OVP < 27V, and can not be damaged.

在 90~264Vac 输入时空载和满载情况下, 输出过压保护大于 27V,小于 22V, 且不能损坏。

5.4. Over temperature protection/过温保护

When the temperature exceeds 110±5°C, turn off the output voltage and automatically recover when the temperature drops to 75°C.

当温度超过 110±5°C时, 关闭输出电压, 温度下降到 75°C后自动恢复。

6. Environment Requirements/环境要求

6.1. Operating Temperature and Relative Humidity/操作温/湿度要求

Operating temperature:-30°C to +70°C

工作温度: -30°C to +70°C

Operating Relative humidity:10%RH to 90%RH

工作湿度: 10%RH to 90%RH

6.2. Storage Temperature and Relative Humidity/存储温/湿度要求

Storage Temperature:-40°C to +80°C

储存温度: -40°C to +85°C

Storage relative humidity:10%RH to 95%RH non-condensing

存储湿度: 10%RH to 95%RH

6.3. Sea level shall be low 2.000 meters/低于 2000 米.

6.4. Vibration/振动

10 to 500Hz sweep at a constant acceleration of 2.0G(Displacement amplitude:

3.5mm),10 minutes per cycle, 60 minutes on the X, Y and Z axis.

以 2.0G 恒定加速度(位移幅值:3.5mm)扫频 10 - 500Hz, 每循环 10 分钟, X、Y、Z 轴 60 分钟。

7. Reliability Requirements/可靠性要求

7.1. Burn-in/老化

The power supply shall be burn-in for 2 Hours under rated input and 80% Full load at 40°C

±5°C.

电源在 40°C ±5°C 额定输入、80%满负荷情况下老化 2 小时。

7.2. E-caps lifetime

The E-caps used in this power supply must be with lifetime of 3 years @ 25°C of full load. @ 200Vac / 60Hz and / or 240Vac /50Hz.

本电源使用的电解电容寿命必须在 25°C 满负荷时使用寿命为 3 年。@ 200Vac / 60Hz 和/或 240Vac /50Hz。

7.3.MTBF :

≥200 K Hrs MIL-HDBK-217F (25°C).

平均无故障时间 20 万小时以上, 标准 MIL-HDBK-217F (25°C)。

8. EMI/EMS Standards/EMI/EMS 标准

8.1. EMI Standards/EMI 标准

| EMI | Standards | Margin Measurements |
|---------------------|------------------------------------|---------------------|
| Radiated Emission | EN55032 EN55035 GB/T9254 GB17625.1 | ≥3dB |
| Conduction Emission | EN55032 EN55035 GB/T9254 GB17625.1 | ≥3dB |

8.2. EMS Standards/EMS 标准

8.2.1.EN 61000-4-2,electrostatic discharge(ESD) requirement/静电抗扰度要求

| Discharge characteristic/静电规格 | Test level/测试条件 | Test criteria/测试标准 |
|-------------------------------|-----------------|--------------------|
| Air discharge/空气放电 | +/- 8KV | A |
| Contact discharge/接触放电 | +/- 4KV | A |

8.2.2.EN 61000-4-3,radiated electromagnetic field susceptibility(rs)/辐射骚扰场强

| Test level/测试条件 | Test criteria/测试标准 |
|-----------------------------------|--------------------|
| 10V/m (r.m.s) | A |
| 30-1000MHz,80% AM(1KHz) sine-wave | |

8.2.3.EN 61000-4-4,electric fast transients(burst) immunity requirement/电快速瞬变脉冲群

| Coupling/测试端口 | Test level/测试条件 | Test criteria/测试标准 |
|---------------|-----------------|--------------------|
| AC-input/交流输入 | 0.5KV | A |
| AC-input/交流输入 | 1KV | A |

8.2.4.EN 61000-4-5,surge capability requirement/浪涌抗扰度要求

| Surge voltage/雷击电压 | Test criteria/测试标准 |
|-----------------------------|--------------------|
| Common mode/共模 +/- 2KV | A |
| Differential mode/差模 +/-4KV | |

8.2.5.EN 61000-4-6, Induced radio frequency fields conducted disturbances immunity requirement/电源端子传导骚扰实验

| Test level/测试条件 | Test criteria/测试标准 |
|-----------------|--------------------|
|-----------------|--------------------|

| | |
|-------------------------|---|
| 3V | A |
| 0.15-30 MHz,80%AM(1KHz) | |

8.2.6. Assessment criteria /评估标准

| Acceptance criteria 可接受标准 | Performance 性能 |
|------------------------------|---|
| A | <p>Agreed operational behavior within the specified limits 性能不允许变化；如果性能会发生变化，则变化的范围在产品规格书规定的范围内。</p> |
| B | <p>Time limited functional diminishment or malfunction during the tests is permitted. The function is self-reactivated by the unit following completion of the tests. 设备在测试过程中,性能降低允许在产品规格书要求范围内,干扰消除后,设备能恢复正常,不允许出现复位和任何方式的人工干预。</p> |
| C | <p>Malfunction is permitted .The function can be reactivated either by reconnection to the mains or by operator intervention. 在测试过程中，设备允许出现业务中断，测试完毕后允许自行恢复或者人工干预恢复（包括硬件上干预）；测试中只允许初级防护器件损坏，并且更换损坏的初级防护器件后，设备能恢复正常</p> |

9. Safety Standards/安规标准

9.1. Dielectric Strength(Hi-pot)/介电耐压强度(高压)

I/P- O/P: 3KVac / 5mA max. / 60 second .

输入对输出: **3KVac / 5mA max. / 60 秒.**

I/P-FG: 2KVac / 5 mA max. / 60 second .

输入对地: **2KVac / 5 mA max. / 60 秒**

O/P-FG: 0.5K Vac / 5 mA max. / second.

输出对地: **0.5KVac / 5 mA max. / 60 秒.**

9.2. Leakage Current/漏电流

3.5mA max. at 250Vac / 50Hz.

输入 **250V AC**,漏电流小于 **3.5mA**。

9.3. Insulation Resistance/绝缘阻抗

I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25°C/ 70% RH

输入对输出、输入对地、输出对地, 在 **25°C 70%**的湿度分别施加 **500Vdc** 进行测试, 阻抗大于 **100兆欧姆**.

9.4. Regulatory Standards/安规标准

| Type/安规 | Country/国家 | Standard/标准 | State/状况 | Note/备注 |
|---------|------------|-------------|----------|---------|
| CCC | China | GB4943.1 | Meet | |
| CE | Europe | EN62368-1 | Meet | |
| FCC | Europe | EN62368-1 | Meet | |

10. Mechanical Outline Drawing/外观示意图

215L*115W*30H mm

