

ROCPU Product features

Voltage: < 12V

Current: < 20mA

Conduction time: 2ms

Closed circuit resistance: < 10m ohm

Open circuit resistance: > 10m ohm

High temperature resistance: 120 degrees

Terminal tension: 500gf / min



Humidity: 25~95%RH

Operating life: 100000 times

Product features

- 1.TPSW-460 is double ball type single direction tilt induction trigger switch.
2. When the electric end of the product guide (foot less) is tilted and the tilt Angle is greater than 10 degrees, the product is in the open, (OFF) state. When the horizontal state of the product is tilted and the trigger end (gold-plated pin end) is lower than the horizontal and the tilt Angle is greater than 10 degrees, the product is in the closed, (ON) state.
3. When placed horizontally, shaking can be easily triggered, and when there is no foot down, shaking is not easy to trigger.
4. The products of this specification are completely sealed, waterproof and dustproof.
5. Under normal circumstances, the switching life can reach 100,000 times.
6. This product is made of environment-friendly metal material with stable performance.

⑦	Heat shrinkable tube	1	Pet heat shrinkable tube	
⑥	Rubber stopper	1	PLC	
⑤	BALL	1	Brass	Nickel
④	BALL	1	Brass	Silver
③	PIN B	1	Brass	Gold
②	PIN A	1	Brass	Nickel
①	Copper pipe	1	Brass	Nickel
ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING

A4					COMMON TOLERANCE: X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3						DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TPSW-460	
A2						DATE	2017	APPROVAL BY	ALEN	Https: www.rocpcu.tw	
A1						ROCPU TECHNOLOGY CO.,LTD					
REV.	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				
		A		B	C	D	E	F	G		