


REV.	ECN NO.	DESCRIPTION	DATE	DESIGN

General tolerances(mm)														0.1/10 ±2°
0 ~ 3	>3 ~ 6	>6 ~ 10	>10 ~ 18	>18 ~ 30	>30 ~ 50	>50 ~ 80	>80 ~ 120	>120 ~ 180	>180 ~ 250	>250 ~ 315	>315 ~ 400	>400 ~ 500	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	



Product model	PIN	A	B
A350KA-2P1G36	2	7.80	3.50
A350KA-3P1G36	3	11.30	7.00
A350KA-4P1G36	4	14.80	10.50
A350KA-5P1G36	5	18.30	14.00
A350KA-6P1G36	6	21.80	17.50
A350KA-7P1G36	7	25.30	21.00
.....			
A350KA-24P1G36	24	3.5xN+0.8	3.50x(N-1)

UL Standard	B	C	D
Rated Voltage(V)/Current(A)	300/8	/	300/8
IEC Standard			
Overvoltage Category/Pollution Degree	II/2		
Rated Voltage(V)/Current(A)	250/7		
Rate Impulse Voltage(KV)	2.5		
Torque Tightening(N·m/Lb.in)	M2, 0.2/1.77		
Wire Range(rigid and flexible)(mm²/AWG)	0.5~1.5/28~16		
Pitch(mm)/Poles	3.50/N=02~24P		
Stripping length(mm)	6-7		
Operating temperature(°C)	-40C°~+105C°		
Conform to RoHS	Yes		

5	Clamp	Copper Alloy	Sn Plated
4	Screw	Steel	M2/Zn Plated
3	Cage	Copper Alloy	M2/Ni Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

TOLERANCE		深圳聚兴泰电子科技有限公司 Shenzhen Juxingtai Electronic Technology Co., Ltd			
		PART NO.	TITLE:		
		A350KA-NP1G36	Socket-type terminal		
UNITS	mm	DESIGN: Ethan	MANUFACTURE DWG		
MATERILA	— — —	CHED: Olvia		SCALE	SHEET
FINISH	— — —	APPD: Ava		N:A	1/1