



SMBJ Series



600W, 5.0V - 180V Surface Mount Transient Voltage Suppressor

FEATURES

- For surface mounted applications in order to optimize board space.
- Glass passivated junction
- Low inductance
- Plastic package has Underwriters Laboratory Fammability Classification 94V-0
- High temperature soldering : 260°C /10 seconds at terminals

MECHANICAL DATA

- Case: SMB(DO-214AA)
- Terminals: Solder plated,solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode end



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C Ambient temperature unless otherwise specified. Resistive or inductive load,
For Capacitive load derate current by 20%.

Parameter	Symbol	Value	Unit
Peak pulse power dissipation with a 10/1000 μ s waveform ⁽¹⁾ Fig.4	P _{PPM}	600	W
Peak pulse current with a waveform ⁽¹⁾	I _{PPM}	See next table	A
Power dissipation on infinite heatsink at T _L =75°C	P _D	5.0	W
Peak forward surge current 8.3 ms single half sine-wave uni-directional only ⁽²⁾	I _{FSM}	100	A
Operating junction and storage temperature range	T _J , T _{STG}	-55 to +150	°C

Note:

(1) Non-repetitive current pulse per Fig.5 and derated above T_A=25°C per Fig.1.

(2) Measured on 8.3 ms single half sine-wave or equivalent square wave, duty cycle=4 pulses per minute maximum.



Ratings And Characteristics Curves ($T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted)

Part Number (Uni)	Part Number (Bi)	Marking Code		Breakdown Voltage $V_{BR}@I_T$			Maximum Reverse Leakage $I_R@V_{RWM}$ (μA)	Working Peak Reverse Voltage V_{RWM} (V)	Maximum Reverse Surge Current $I_{PP}(A)$	Maximum Clamping Voltage $V_C@$ $I_{PP}(V)$
		Uni	Bi	Min(V)	Max(V)	$I_T(mA)$				
SMBJ5.0A	SMBJ5.0CA	KE	AE	6.4	7.0	10	800	5	65.22	9.2
SMBJ6.0A	SMBJ6.0CA	KG	AG	6.67	7.37	10	800	6	58.3	10.3
SMBJ6.5A	SMBJ6.5CA	KK	AK	7.22	7.98	10	500	6.5	53.6	11.2
SMBJ7.0A	SMBJ7.0CA	KM	AM	7.78	8.6	10	200	7	50.0	12
SMBJ7.5A	SMBJ7.5CA	KP	AP	8.33	9.21	1	100	7.5	46.5	12.9
SMBJ8.0A	SMBJ8.0CA	KR	AR	8.89	9.83	1	50	8	44.1	13.6
SMBJ8.5A	SMBJ8.5CA	KT	AT	9.44	10.4	1	10	8.5	41.7	14.4
SMBJ9.0A	SMBJ9.0CA	KV	AV	10.0	11.1	1	5	9	39.0	15.4
SMBJ10A	SMBJ10CA	KX	AX	11.1	12.3	1	5	10	35.3	17
SMBJ11A	SMBJ11CA	KZ	AZ	12.2	13.5	1	1	11	33.0	18.2
SMBJ12A	SMBJ12CA	LE	BE	13.3	14.7	1	1	12	30.2	19.9
SMBJ13A	SMBJ13CA	LG	BG	14.4	15.9	1	1	13	27.9	21.5
SMBJ14A	SMBJ14CA	LK	BK	15.6	17.2	1	1	14	25.9	23.2
SMBJ15A	SMBJ15CA	LM	BM	16.7	18.5	1	1	15	24.6	24.4
SMBJ16A	SMBJ16CA	LP	BP	17.8	19.7	1	1	16	23.1	26
SMBJ17A	SMBJ17CA	LR	BR	18.9	20.9	1	1	17	21.8	27.6
SMBJ18A	SMBJ18CA	LT	BT	20.0	22.1	1	1	18	20.6	29.2
SMBJ20A	SMBJ20CA	LV	BV	22.2	24.5	1	1	20	18.6	32.4
SMBJ22A	SMBJ22CA	LX	BX	24.4	26.9	1	1	22	16.9	35.5
SMBJ24A	SMBJ24CA	LZ	BZ	26.7	29.5	1	1	24	15.4	38.9
SMBJ26A	SMBJ26CA	ME	CE	28.9	31.9	1	1	26	14.3	42.1
SMBJ28A	SMBJ28CA	MG	CG	31.1	34.4	1	1	28	13.2	45.4
SMBJ30A	SMBJ30CA	MK	CK	33.3	36.8	1	1	30	12.4	48.4
SMBJ33A	SMBJ33CA	MM	CM	36.7	40.6	1	1	33	11.3	53.3
SMBJ36A	SMBJ36CA	MP	CP	40.0	44.2	1	1	36	10.4	58.1
SMBJ40A	SMBJ40CA	MR	CR	44.4	49.1	1	1	40	9.3	64.5
SMBJ43A	SMBJ43CA	MT	CT	47.8	52.8	1	1	43	8.7	69.4
SMBJ45A	SMBJ45CA	MV	CV	50.0	55.3	1	1	45	8.3	72.7
SMBJ48A	SMBJ48CA	MX	CX	53.3	58.9	1	1	48	7.8	77.4
SMBJ51A	SMBJ51CA	MZ	CZ	56.7	62.7	1	1	51	7.3	82.4
SMBJ54A	SMBJ54CA	NE	DE	60.0	66.3	1	1	54	6.9	87.1
SMBJ58A	SMBJ58CA	NG	DG	64.4	71.2	1	1	58	6.4	93.6
SMBJ60A	SMBJ60CA	NK	DK	66.7	73.7	1	1	60	6.2	96.8
SMBJ64A	SMBJ64CA	NM	DM	71.1	78.6	1	1	64	5.8	103
SMBJ70A	SMBJ70CA	NP	DP	77.8	86.0	1	1	70	5.3	113
SMBJ75A	SMBJ75CA	NR	DR	83.3	92.1	1	1	75	5.0	121
SMBJ78A	SMBJ78CA	NT	DT	86.7	95.8	1	1	78	4.8	126
SMBJ85A	SMBJ85CA	NV	DV	94.4	104	1	1	85	4.4	137



Ratings And Characteristics Curves ($T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted)

Part Number (Uni)	Part Number (Bi)	Marking Code		Breakdown Voltage $V_{BR}@I_T$			Maximum Reverse Leakage $I_R@V_{RWM}$ (μA)	Working Peak Reverse Voltage V_{RWM} (V)	Maximum Reverse Surge Current $I_{PP}(A)$	Maximum Clamping Voltage $V_C@I_{PP}(V)$
		Uni	Bi	Min(V)	Max(V)	$I_T(\text{mA})$				
SMBJ90A	SMBJ90CA	NX	DX	100	111	1	1	90	4.1	146
SMBJ100A	SMBJ100CA	NZ	DZ	111	123	1	1	100	3.7	162
SMBJ110A	SMBJ110CA	PE	EE	122	135	1	1	110	3.4	177
SMBJ120A	SMBJ120CA	PG	EG	133	147	1	1	120	3.1	193
SMBJ130A	SMBJ130CA	PK	EK	144	159	1	1	130	2.9	209
SMBJ150A	SMBJ150CA	PM	EM	167	185	1	1	150	2.5	243
SMBJ160A	SMBJ160CA	PP	EP	178	197	1	1	160	2.3	259
SMBJ170A	SMBJ170CA	PR	ER	189	209	1	1	170	2.2	275
SMBJ180A	SMBJ180CA	PT	ET	200	220	1	1	180	2.1	292
SMBJ190A	SMBJ190CA	PV	EV	211	234	1	1	190	2.0	307
SMBJ200A	SMBJ200CA	PX	EX	224	247	1	1	200	1.9	324
SMBJ210A	SMBJ210CA	PZ	EZ	233	258	1	1	210	1.8	337
SMBJ220A	SMBJ220CA	QE	FE	246	272	1	1	220	1.7	356
SMBJ250A	SMBJ250CA	QG	FG	279	309	1	1	250	1.5	405
SMBJ300A	SMBJ300CA	QK	FK	335	371	1	1	300	1.3	486
SMBJ350A	SMBJ350CA	QM	FM	391	431	1	1	350	1.1	567
SMBJ400A	SMBJ400CA	QP	FP	447	494	1	1	400	0.9	648
SMBJ440A	SMBJ440CA	QR	FR	492	543	1	1	440	0.8	713

Note:

① Surge waveform: 10/1000 μs

V_{RWM} : Stand-off voltage -- Maximum voltage that can be applied

V_{BR} : Breakdown voltage

V_C : Clamping voltage -- Peak voltage measured across the suppressor at a specified I_{PP}

I_R : Reverse leakage current



Ratings And Characteristics Curves ($T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted)

Fig.1 Derating Curve




Fig.2 Maximum Non-repetitive Forward Surge Current Unidirectional only




Fig.3 Steady State Power Derating Curve




Fig. 4 Peak Pulse Power Rating Curve




Fig.5 Clamping Power Pulse Waveform





Fig.6 Mounting PAD Layout





Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from XINNUO
- XINNUO reserves the right to make changes to this document and its products and specifications
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications.

XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown here in are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.