



# **SUMMARY**

#### # Wires



Image is for illustrative purpose only

Series 0B

Termination type No contacts / Accessory

IP rating (

AWG wire size 0.00 - 0.00

Cable Ø 3.50 - 3.90 mm

**Status** active

#### **Download**

Request a quote

Catalog

# **TECHNICAL DETAILS**

## **Mechanics**

Shell Style/Model GMA\*: Bend relief Orange

**Keying** No keying

Housing Material Silicone elastomer VMQ

Variant S : Orange

Weight .46 g

### **Performance**

Configuration

Insulator

**Rated Current** 


## **Others**

Temp (min / max):  $-60^{\circ}$ C /  $+200^{\circ}$ C

Temperature range in water steam: +140°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# **DRAWINGS**



No keying

#### **Dimensions**

	Α	L
mm.	3.5	27
in.	0,14	1,06

# **RECOMMENDED BY LEMO**

#### **Tools**

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.